



TELLUS POWER GREEN DC FAST CHARGERS



TELLUS POWER GREEN DC FAST CHARGER

180 kW Charging Station



**Model :
TP-EVPD-180kW**

- ✓ DCFC and HPC System with 1000VDC
- ✓ Powerful Compact All-In-One Charger
- ✓ Simple Air-Cooled Power Modules
- ✓ Easy to Maintain
- ✓ Parallel Charging Feature
- ✓ Liquid Cooled Cables
- ✓ OCPP 1.6J
- ✓ Credit Card Reader
- ✓ Cord Management

TELLUS POWER GREEN DC FAST CHARGER

180 kW Charging Station



**Model :
TP-EVPD-180kW**



Product #	TP5-180-480	HPC-180-480
Model #	TP-EVPD-180kW	
Maximum Power	180 kW	
Output Voltage	150 – 1000 VDC	
Max Output Current	Up to 200A / 300A	Up to 500A
Input	480V (3P + N + PE), 60 Hz	
Input Current Breaker Rating	240A 300A	
Power Factor	>0.98	
Efficiency	>94% at nominal output power	
Connector Options	CCSI and CCS1 CCSI and CHAdeMO	CCSI and CCS1 CCSI and CHAdeMO
CCS Cable	200A (Standard) 300A (Optional)	500A (Liquid Cooled)
CHAdeMO Cable	125A (Standard) Or 200A	
Cycle Mode	1 x 180kW (Max: 200A)	1 x 180kW (Max: 450A)
Parallel Mode	2 x 90kW (Max: 200A)	2 x 90kW (Max: 250A)
Charging Protocol Standards	Mode 4, IEC-61851, ISO-15118, DIN 70121 Mode 4, CHAdeMO 0.9, 1.0	
Connector cable length	CCS - 13 ft (4 m) CHAdeMO – 16ft (5 m) Cable Retractor Included	
Weight	880 lbs (400 kg)	950 lbs (430 kg)
Dimensions (L x D x H)	29.5" x 26.5" x 73"	41.38" x 37.40" x 86.30"
Insulation (input – output)	>2.5 kV	
Ingress Protection	NEMA 3S, IK10	
Altitude	<6,600ft (2,000m)	
Operating temperature	-30°C to 55°C (-22°F to 131°F)	
Working Storage Humidity	≤ 95% RH ≤ 99% RH (Non-condensing)	
Display	10" touch screen	
Communication Protocol	Ethernet, 4G/WiFi OCPP 1.6J	
Access Control	RFID : ISO/IEC 14443A/B Credit Card Reader (Optional)	
Metering	DC kWh meter per each connector	
Power Electronics Cooling	Air Cooled	
Regulatory Compliance	UL-2202 EMC: EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012	
Electrical Safety: GFCI	RCD 20 mA Type A	
Electrical Safety: Surge Protection	20 kA	
Electrical Safety General	Over Voltage, Under Voltage, Over Current, Missing Ground	
Electrical Safety: Output Short	Output power disabled when output is short circuited	
Electrical Safety Temperature	Temperature Sensors @ Charge Coupler and Power Electronics	
Emergency Stop	Disables output power with emergency stop button	